



PRODUCT SHEET

RAMPMATIC® GSE TIRES

TIRES THAT NEVER NEED TO TREAD LIGHTLY

THE MOST RELIABLE GSE TIRES ON THE MARKET

Whether it's blistering hot, snow is sticking, or the rain is relentless, it is more important than ever for GSE to perform at optimal efficiency. Designed to handle high heat, freezing cold, and the most difficult ramp conditions, **RAMPMATIC®** tires from **SAGE PARTS** provide maximum performance.



RIB TREAD



M+S TREAD

Available with Rib or M+S tread, **RAMPMATIC®** tires are specifically designed for long tread life and maximum sidewall protection.

RAMPMATIC® tires are made of a proprietary formulated rubber compound and a specially designed sidewall that resists damage and produces the lowest cost per engine hours regardless of harshest operating and ramp conditions.

FEATURES

- MAXIMUM TRACTION IN ALL SURFACE CONDITIONS
- DESIGNED TO OUT PERFORM OTHER BRANDS
- BETTER PERFORMANCE MEANS BETTER FUEL ECONOMY
- DESIGNED WITH A SPECIAL RIM GUARD FOR ENHANCED SIDEWALL PROTECTION
- INCREASED TREAD DEPTH FOR LONGER LIFE
- SMOOTHER OVERALL RIDE

REINFORCED SIDEWALL FOR IMPROVED STABILITY AND IMPACT RESISTANCE

SPECIAL FEATURES

RAMPMATIC® tires are designed for reliability, optimal performance, and a longer service life. This helps reduce downtime cost, fuel consumption, and lower the total cost of ownership.

TREAD DEPTH AND CONSTRUCTION

RAMPMATIC® tires are made with a special formulated compound to run cooler and have high wear resistance. Wear resistance is enhanced with a higher tread depth, which improves traction and stability.

RIM GUARD

RAMPMATIC® tires have a specially designed rim guard that helps protect the tire from damage from foreign objects and debris.

REINFORCED SIDEWALL

The reinforced sidewall of RAMPMATIC® tires enhances durability and heightens resistance to impacts. It also improves the stability of the vehicle and creates a smoother ride.



TIRE SIZES AND SPECIFICATIONS

AVAILABLE SIZES

| SIZE | TYPE | RIM WIDTH | INFLATED DIMENSIONS +/-2% | | | | NSD | | PLY | INFLATION PRESSURE | | LOAD CAPACITY | | | | | | | |
|----------------------------|------|-----------|---------------------------|-----|---------------|-----|-------------|------|-----|--------------------|-----|---------------|-------|------------------|-------|-------------------|-------|-------------------|-------|
| | | | OD INFLATED | | SECTION WIDTH | | TREAD DEPTH | | | psi | kPa | STATIONARY | | 6 mph 10 km/h | | 15 mph 25 km/h | | 30 mph 50 km/h | |
| | | | in | mm | in | mm | in | mm | | | | lbs | kg | lbs | kg | lbs | kg | lbs | kg |
| 600X9 | TT | 4.00 | 21.50 | 546 | 6.80 | 173 | 20/32 | 16.5 | 10 | 125 | 862 | 4,728 | 2,145 | 3,792 | 1,720 | 2,954 | 1,340 | 2,425 | 1,100 |
| 650X10 | TT | 5.00 | 24.00 | 604 | 7.25 | 182 | 20/32 | 16.5 | 12 | 140 | 965 | 7,451 | 3,380 | 5,141 | 2,332 | 3,946 | 1,790 | 3,317 | 1,505 |
| 165X13 | TL | 4.50 | 23.30 | 590 | 6.30 | 160 | 20/32 | 16.5 | 10 | 65 | 448 | 4,321 | 1,960 | 4,155 | 1,885 | 3,174 | 1,440 | 2,668 | 1,210 |
| 700X15 | TT | 6.00 | 29.70 | 755 | 7.80 | 198 | 22/32 | 17.5 | 12 | 75 | 517 | 4,266 | 1,935 | 4,012 | 1,820 | 3,307 | 1,500 | 2,811 | 1,275 |
| 800X165 | TL | 6.00 | 29.40 | 747 | 8.50 | 217 | 19/32 | 14 | 8 | 65 | 448 | 3,836 | 1,740 | 3,395 | 1,540 | 2,657 | 1,205 | 2,425 | 1,110 |
| 875X165 | TL | 6.75 | 30.12 | 765 | 9.00 | 230 | 22/32 | 17.5 | 10 | 80 | 552 | 3,990 | 1,810 | 3,704 | 1,680 | 3,109 | 1,410 | 2,696 | 1,223 |
| 875X165 MUD AND SNOW | TL | 6.75 | 30.12 | 765 | 9.00 | 230 | 23/32 | 18.5 | 10 | 80 | 552 | 3,990 | 1,810 | 3,704 | 1,680 | 3,109 | 1,410 | 2,696 | 1,223 |

TL — Tubeless
TT — Tube and flap included